Post Top V416101, V416102



Description

The Post Top is a range of high performance luminaires suitable for parks and walkways.

Environment

Outdoor

Installation

Designed to be pole mounted

Application

For use in parks, walkways and other similar applications.











| Voltage | AC220-240V 50-60Hz |
|----------------|--|
| Power Factor | >0.9 |
| Light Source | LED |
| CCT | 3500K |
| LED Lifetime | 50,000hrs |
| Operating temp | -20°C to 30°C |
| Materials | Die cast aluminium housing black or charcoal finish Polycarbonate diffuser |
| | |

Light Data

| Lumens per Watt | 115lm/W |
|-----------------|---------|
| Light Source | LED |
| CRI | 80 |
| Distribution | 120° |

MG Lites, 4 Denaby Lane Industrial Estate, Coalpit Road, Denaby, Doncaster, South Yorkshire, DN12 4LH

Post Top V416101- V416102



Product Variants

| Product Code | Finish | System Power (W) | System efficacy (lm/W) | Lumens (lm) | CCT (K) | Diameter mm | Height mm |
|--------------|----------|------------------------|------------------------------|----------------|------------|----------------|--------------|
| V416101 | Charcoal | 60W | 115 | 7200 | 3500K | 420 | 390 |
| V416102 | Black | 100W | 115 | 12,000 | 3500K | 450 | 526 |

Dimensions





Accessories

| OPTION | CODE |
|-------------------|----------|
| 76mm pole adaptor | AV416101 |
| Photocell control | AV416102 |